MNN. Firemed abers com

CAMBRIDGE INTERNATIONAL EXAMINATIONS

International General Certificate of Secondary Education

MARK SCHEME for the October/November 2013 series

0625 PHYSICS

0625/33

Paper 3 (Extended Theory), maximum raw mark 80

This mark scheme is published as an aid to teachers and candidates, to indicate the requirements of the examination. It shows the basis on which Examiners were instructed to award marks. It does not indicate the details of the discussions that took place at an Examiners' meeting before marking began, which would have considered the acceptability of alternative answers.

Mark schemes should be read in conjunction with the question paper and the Principal Examiner Report for Teachers.

Cambridge will not enter into discussions about these mark schemes.

Cambridge is publishing the mark schemes for the October/November 2013 series for most IGCSE, GCE Advanced Level and Advanced Subsidiary Level components and some Ordinary Level components.



Page 2	Mark Scheme	Syllabus	Paper
	IGCSE – October/November 2013	0625	33

NOTES ABOUT MARK SCHEME SYMBOLS & OTHER MATTERS

M marks

are method marks upon which further marks depend. For an M mark to be scored, the point to which it refers **must** be seen in a candidate's answer. If a candidate fails to score a particular M mark, then none of the dependent marks can be scored.

B marks

are independent marks, which do not depend on other marks. For a B mark to scored, the point to which it refers must be seen specifically in the candidate's answers.

A marks

In general A marks are awarded for final answers to numerical questions. If a final numerical answer, eligible for A marks, is correct, with the correct unit and an acceptable number of significant figures, all the marks for that question are normally awarded. It is very occasionally possible to arrive at a correct answer by an entirely wrong approach. In these rare circumstances, do not award the A marks, but award C marks on their merits. However, correct numerical answers with no working shown gain all the marks available.

C marks

are compensatory marks in general applicable to numerical questions. These can be scored even if the point to which they refer are not written down by the candidate, provided subsequent working gives evidence that they must have known it. For example, if an equation carries a C mark and the candidate does not write down the actual equation but does correct substitution or working which shows he knew the equation, then the C mark is scored. A C mark is not awarded if a candidate makes two points which contradict each other. Points which are wrong but irrelevant are ignored.

Brackets ()

around words or units in the mark scheme are intended to indicate wording used to clarify the mark scheme, but the marks do not depend on seeing the words or units in brackets e.g. 10 (J) means that the mark is scored for 10, regardless of the unit given.

Underlining

indicates that this <u>must</u> be seen in the answer offered, or something very similar.

OR/or

indicates alternative answers, any one of which is satisfactory for scoring the marks.

e.e.o.o.

means "each error or omission".

o.w.t.t.e.

means "or words to that effect".

c.a.o.

correct answer only

Spelling

Be generous about spelling and use of English. However, do not allow ambiguities e.g. spelling which suggests confusion between reflection/refraction/diffraction or thermistor /transistor/transformer.

Not/NOT

indicates that an incorrect answer is not to be disregarded, but cancels another otherwise correct alternative offered by the candidate i.e. right plus wrong penalty applies.

Ignore

indicates that something which is not correct or irrelevant is to be disregarded and does not cause a right plus wrong penalty.

Page 3	Mark Scheme	Syllabus	Paper
	IGCSE – October/November 2013	0625	33

e.c.f.

meaning "error carried forward" is mainly applicable to numerical questions, but may in particular circumstances be applied in non-numerical questions. This indicates that if a candidate has made an earlier mistake and has carried an incorrect value forward to subsequent stages of working, marks indicated by e.c.f. may be awarded, provided the subsequent working is correct, bearing in mind the earlier mistake. This prevents a candidate being penalised more than once for a particular mistake, but **only** applies to marks annotated e.c.f.

Significant figures

Answers are normally acceptable to any number of significant figures \geq 2. Any exceptions to this general rule will be specified in the mark scheme.

Units

Deduct one mark for each incorrect or missing unit from an answer that would otherwise gain all the marks available for that answer: maximum 1 per question.

Arithmetic errors

Deduct one mark if the **only** error in arriving at a final answer is clearly an arithmetic one.

Transcription errors

Deduct one mark if the only error in arriving at a final answer is because given or previously calculated data has clearly been misread but used correctly.

Fractions Only accept these where specified in the mark scheme.

	Page 4			Mark Scheme	Syllabus	Paper	
				IGCSE – October/November 2013	0625	33	
1	(a)	(i)	(met	cals/they are) (good) conductors (of heat)		B1	[1]
		(ii)		ot end) molecules vibrate (more) lectrons identified as mechanism of conduction		B1	
				ecules collide with their neighbours lectrons move faster/have more energy		B1	
				gy/vibration passed on lectrons pass on energy/reach far end/free to move		B1	[3]
	(b)	imn dete	nerse ermin	e mass of spoon (condone weigh provided word ma spoon in water/liquid e increase in volume/overflow or density = mass/volume	iss is used in answ	er) B1 B1 B1 B1	[4]
						[Tota	l: 8]
2	(a)	(<i>W</i> 2.5	, -	g or 0.25 × 10 or 250 × 10 or 2500		C1 A1	[2]
	(b)	(i)		of proportionality or (the point where) proportionality nsion stops or Hooke's Law no longer obeyed (cond		d B1	[1]
		(ii)		lient or numbers from graph divided e.g. 4.5 ÷ 10 N/cm or 45 N/m		C1 A1	[2]
	(c)	(i)	0 (N) or zero or no net force etc. (ignore absent unit; wr	ong unit loses mar	k) B1	[1]
		(ii)	2.	0.9 N (accept 0.8 N < value < 1.0 N) (a =) F/m or 0.90/0.12 (e.c.f. from 2(c)(i)) 7.5 m/s² (e.c.f. from 2(c)(i))		B1 C1 A1	[1] [2]
							ıl: 9]
3	(a)			$F \times d$ or 640×3.5 2 or more sig. figs.		C1 A1	[2]
	(b)	(i)	(<i>E</i> = 7500) <i>VIt</i> or 75 × 25 × 4.0 or 75 × 100 (accept (<i>E</i> =) <i>VQ</i>	and Q = It)	C1 A1	[2]
		(ii)	(effic	ciency =) $\frac{\text{(useful)energy output}}{\text{energy input}}$ (× 100%) or 2240/7	7500		
			(acc	energy input ept power for energy) (e.c.f. from 3(a)(i) or 3(b)(i)) or 0.30 or 0.299 or 30% or 29.9% (e.c.f. from 3(a)(i)		C1 A1	

		ige c	,	IGCSE – October/November 2013	0625	33			
	(c)	any two from: electrical heating friction W.D. lifting supports sound							
						[Tota	al: 8]		
4	(a)	(i)	(GPI 34 J	E =) mgh or 0.40 × 10 × 8.5 (accept 9.8 for 10)		C1 A1	[2]		
		(ii)	or 2	= GPE in any form or ½ <i>mv</i> ² or 2 <i>gh</i> × 10 × 8.5 (e.c.f. from 4(a)(i)) :) 170 or (<i>v</i> =)√170		C1			
				f. from 4(a)(i)) n/s e.c.f. from 4(a)(i)		C1 A1	[3]		
	(b)			air resistance or friction with air (ignore wind for air) nergy lost as heat or more KE needed to overcome		B1 B1	[2]		
	(c)		transformed to thermal energy/heat or friction/air resistance slows parachutist dowr						
		 or lost to air particles (not KE (accept KE of air), not GPE → KE → heat; ignore sound) 					[1]		
5	(a)	(nu	clear)	fusion		B1	[1]		
	(b)	(i)		ller (surface) area ept thinner, narrower(at top), ignore reference to lid)	B1	[1]		
		(ii)		aratus: black object, white object, thermometer(s)/ba/level of water in vessel	all-bearing with	B1			
			sour	ce of heat e.g. Sun/radiant heater (condone light bu	ulb/Bunsen burne	r) B1			
				on: (fill cans with water and) measure temperature r pare volumes of water	ise or wax melts o	or B1			
			incre	ervation: water in black can (better absorber) has gr ease / wax melts first / less water : emission experiment gains max. 2	eater temperature	e B1	[4]		
						[Tota			

Syllabus

Paper

	Page 6			Mark Scheme	Syllabus	Paper			
				IGCSE – October/November 2013	0625	33			
6	(a)	(Q/E 1.2 × (c =) (allow	C1 C1						
		2.5 × (allow	A1	[4]					
	(b)	(stud	(student's value) too large and heat lost to surroundings/kettle/evaporation						
						[Tota	il: 5]		
7	(a)	$n = \sin i / \sin r$ or $n = \sin r / \sin i$ or $(\sin i =) 1.5 \sin 40(^\circ) i$ or $(\sin r =) 1.5 \sin 40(^\circ)$ or 25° 0.9641 75/74.6 $^\circ$ to 2 or more sig. figs.					[3]		
	(b)			$f\lambda$ or $3.8 \times 10^{14} \times 5.3 \times 10^{-7} \times 10^{8}$ m/s to 2 or more sig. figs.		C1 A1	[2]		
		3	3.02	nv or 1.5 × 2.0/2.01/2.014 × 10 ⁸ (e.c.f. from 7(b)(i)) × 10 ⁸ m/s (accept 3 or 3.0 × 10 ⁸ m/s only with world f. from 7(b)(i))	king)	C1 A1	[2]		
	(c)	wave(front) hits/enters the plastic at the same time or incident ray perpendicular along normal/at 90° or i = 0° (condone it doesn't hit at an angle) wave(front) all slows down at the same time or refracted ray perpendicular normal 90° or r = 0° by calculation							
						[Tota			
8	(a)			wave rectified trace (ignore horizontal lines) contal lines and wavelength same and amplitude sa	me/slightly reduce	M1			
				A_0 by eye)		A1	[2]		
				fier or suitable device or produce d.c. (from a.c. for done flashing lamp of some sort)	electronic circuits) B1	[1]		
	(b)	(lamp becomes) dimmer/less bright/flashes on and off							
		less (thermal)energy/heat/power or (thermal) energy etc. for less time or current becomes zero							
						[Tota	l: 5]		

	Pa	Page 7				Paper	
				IGCSE – October/November 2013	0625	33	
9	(a)	alter volta	natin age/e	ng current causes alternating/changing) magnetic fing/changing magnetic field in secondary coil .m.f. induced (in secondary coil) as (on secondary) so greater output	ield (in core)	B1 B1 B1 B1	[4]
	(b)	(i) resistance increases (with/is proportional to length (of cable)) (energy losses) due to resistance (of cables)/heating in cables/electrical work (in cables)/ I^2R					[2]
		(ii) reduced resistance or less heat loss more metal or cables heavier or more pylons or more costly to construct					[2]
						[Tota	ıl: 8]
10	(a)	(i) at least two lines (one left, one right) outside the coil of correct shape or at least two vertical lines inside the coil or two diverging and one central line at top and bottom at least four lines (two left, two right) outside the coil of correct shape or at least two lines (one left, one right) outside the coil of correct shape) and at least two					
				cal lines inside the coil sing or complete loops outside coil gains maximum	n of 1)	A1	[2]
		(ii)	lines	closer where field is stronger o.w.t.t.e. or vice vers	a or spacing of line	es B1	[1]
	(b)		,	(strength of) field ng the resistance) reduces the current		B1 B1	[2]
	(c)	(i)	curve well-	ed path upwards (might curve back to the left) drawn curved path (no straight section and circular	by eye)	B1 B1	[2]
				es in opposite direction to (c)(i) netic field reversed		B1 B1	[2]
						[Tota	ıl: 9]
11	(a)	12 c	ounts	s/min		B1	[1]
	(b)	(i)	72 cc	ounts/min (e.c.f. from 11(a))		B1	
				unts/min (note: if background not subtracted, (i) 84 mpensatory mark)	and (ii) 21 gains	B1	[2]
	(c)	or (e	e.c.f.)	/8 or 3 (half-lives) 21/84 or 1/4 or 2 (half-lives) tes or 4.5 minutes (i.e. background not subtracted b	out otherwise corre	C1 ct) A1	[2]
		[То					