

#### **Cambridge Assessment International Education**

Cambridge International Advanced Subsidiary and Advanced Level

PHYSICS 9702/42

Paper 4 A Level Structured Questions

May/June 2019

MARK SCHEME
Maximum Mark: 100

#### **Published**

This mark scheme is published as an aid to teachers and candidates, to indicate the requirements of the examination. It shows the basis on which Examiners were instructed to award marks. It does not indicate the details of the discussions that took place at an Examiners' meeting before marking began, which would have considered the acceptability of alternative answers.

Mark schemes should be read in conjunction with the question paper and the Principal Examiner Report for Teachers.

Cambridge International will not enter into discussions about these mark schemes.

Cambridge International is publishing the mark schemes for the May/June 2019 series for most Cambridge IGCSE™, Cambridge International A and AS Level and Cambridge Pre-U components, and some Cambridge O Level components.

#### **PUBLISHED**

#### **Generic Marking Principles**

These general marking principles must be applied by all examiners when marking candidate answers. They should be applied alongside the specific content of the mark scheme or generic level descriptors for a question. Each question paper and mark scheme will also comply with these marking principles.

#### **GENERIC MARKING PRINCIPLE 1:**

Marks must be awarded in line with:

- the specific content of the mark scheme or the generic level descriptors for the question
- the specific skills defined in the mark scheme or in the generic level descriptors for the question
- the standard of response required by a candidate as exemplified by the standardisation scripts.

#### **GENERIC MARKING PRINCIPLE 2:**

Marks awarded are always whole marks (not half marks, or other fractions).

#### **GENERIC MARKING PRINCIPLE 3:**

Marks must be awarded **positively**:

- marks are awarded for correct/valid answers, as defined in the mark scheme. However, credit is given for valid answers which go beyond the scope of the syllabus and mark scheme, referring to your Team Leader as appropriate
- marks are awarded when candidates clearly demonstrate what they know and can do
- marks are not deducted for errors
- marks are not deducted for omissions
- answers should only be judged on the quality of spelling, punctuation and grammar when these features are specifically assessed by the question as indicated by the mark scheme. The meaning, however, should be unambiguous.

#### **GENERIC MARKING PRINCIPLE 4:**

Rules must be applied consistently e.g. in situations where candidates have not followed instructions or in the application of generic level descriptors.

© UCLES 2019 Page 2 of 14

### **PUBLISHED**

#### **GENERIC MARKING PRINCIPLE 5:**

Marks should be awarded using the full range of marks defined in the mark scheme for the question (however; the use of the full mark range may be limited according to the quality of the candidate responses seen).

#### **GENERIC MARKING PRINCIPLE 6:**

Marks awarded are based solely on the requirements as defined in the mark scheme. Marks should not be awarded with grade thresholds or grade descriptors in mind.

© UCLES 2019 Page 3 of 14

| Question | Answer   | Marks |
|----------|--|-------|
| 1(a)     | $(F =) GMm / x^2$ , where G is the (universal) gravitational constant  | B1    |
| 1(b)(i)  | angle = $(1.2 \times 10^{-3}) / (8.0 \times 10^{-2}) = 1.5 \times 10^{-2}$ (rad)   | B1    |
| 1(b)(ii) | torque = $1.5 \times 10^{-2} \times 9.3 \times 10^{-10}$   | A1    |
|          | $= 1.4 \times 10^{-11} \mathrm{N}\mathrm{m}$   |       |
| 1(c)(i)  | force $\times 8.0 \times 10^{-2} = 1.4 \times 10^{-11}$  | C1    |
|          | $(G \times 1.3 \times 7.5 \times 10^{-3} \times 8.0 \times 10^{-2}) / (6.0 \times 10^{-2})^2 = 1.4 \times 10^{-11}$  | C1    |
|          | $G = 6.4 \times 10^{-11} \mathrm{N} \mathrm{m}^2 \mathrm{kg}^{-2}$   | A1    |
| 1(c)(ii) | Any one from:  Iaw applies only to point masses/spheres are not point masses  radii of spheres not small compared with separation  spheres may not be uniform  the masses are not isolated  force between L and rod  spheres may be charged/may be electrostatic force (between spheres) | B1    |

© UCLES 2019 Page 4 of 14

| Question  |                   |                       |  | Answer  | Marks |
|-----------|-------------------|-----------------------|--|---|-------|
| 2(a)(i)   | 1. energy         | transfer              | to the syster                          | n by heating  | B1    |
|           | 2. (extern        | nal) work             | done <u>on</u> the                     | system  | B1    |
| 2(a)(ii)  | <u>decrease</u> i | n internal            | energy                                 |   | B1    |
| 2(b)(i)   | no change         | (in intern            | al energy)                             |   | B1    |
|           | (because)         | no chang              | e in tempera                           | ture  | B1    |
| 2(b)(ii)  | work done         | = <i>p</i> ∆ <i>V</i> |  |   | C1    |
|           |                   | = (-)1.6              | $\times$ 10 <sup>5</sup> $\times$ (2.4 | $-0.87) \times 10^{-3}$   |       |
|           |                   | = (-)240              | ) J                                    |   | A1    |
| 2(b)(iii) | first row all     | l correct (           | 0, 480, 480)                           |   | A1    |
|           | second rov        | w all corre           | ect (-1100, 0                          | , –1100)  | A1    |
|           | final colum       | n of third            | row calculat                           | ed correctly from the two values above it, so that the final column adds up to 0                          | A1    |
|           | and               | n in final ı          | row calculate                          | ct, with correct negative sign ed correctly so that it adds to the second column to give the third column | A1    |
|           | 0                 | 480                   | 480                                    |   |       |
|           | -1100             | 0                     | -1100                                  |   |       |
|           | 860               | -240                  | 620                                    |   |       |

| Question  | Answer   | Marks |
|-----------|--|-------|
| 3(a)(i)   | 0.10 s <b>or</b> 0.30 s <b>or</b> 0.50 s <b>or</b> 0.70 s <b>or</b> 0.90 s           | A1    |
| 3(a)(ii)  | 0 <b>or</b> 0.40 s <b>or</b> 0.80 s  | A1    |
| 3(b)(i)   | $\omega = 2\pi / T$  | C1    |
|           | = 2π / 0.40  | A1    |
|           | $= 16  \text{rad s}^{-1}$  |       |
| 3(b)(ii)  | $v_0 = \omega x_0$   | C1    |
|           | = 15.7 × 2.5 × 10 <sup>-2</sup>  | A1    |
|           | $= 0.39 \mathrm{ms^{-1}}$  |       |
|           | or   |       |
|           | tangent drawn at steepest part and working to show attempted calculation of gradient | (C1)  |
|           | leading to $v_0 = 0.39 \text{ m s}^{-1} (allow \pm 0.15 \text{ m s}^{-1})$           | (A1)  |
| 3(b)(iii) | $a_0 = \omega^2 x_0$   | C1    |
|           | $a_0 = (15.7^2 \times 2.5 \times 10^{-2})$   | A1    |
|           | $= 6.2 \text{ m s}^{-2}$   |       |
|           | or   |       |
|           | $a_0 = \omega v_0$   | (C1)  |
|           | $a_0 = 15.7 \times 0.39$   | (A1)  |
|           | $= 6.2 \text{ m s}^{-2}$   |       |

| Question | Answer  | Marks |
|----------|---|-------|
| 3(c)     | period is shorter/lower   | B1    |
|          | Any one from:  • greater spring constant/stiffness  • (restoring) force is greater (for any given extension)  • acceleration is greater (for any given extension)  • greater energy/maximum speed (for a given amplitude) | B1    |

| Question | Answer  | Marks |
|----------|---|-------|
| 4(a)     | product of density and speed  | M1    |
|          | speed of sound in medium  | A1    |
| 4(b)     | Any two from:   | B2    |
|          | <ul> <li>if Z<sub>A</sub> ≫ Z<sub>B</sub> then ratio is (nearly) zero         or if Z<sub>B</sub> ≫ Z<sub>A</sub> then ratio is (nearly) zero         or if Z<sub>B</sub> and Z<sub>A</sub> are very different then ratio is (nearly) zero         or the greater the difference the lower the ratio</li> <li>if Z<sub>A</sub> ≈ Z<sub>B</sub> then ratio is (nearly) 1         or if Z<sub>A</sub> = Z<sub>B</sub> then ratio is 1         or the smaller the difference the closer the ratio to 1 (not 'large')</li> <li>I<sub>T</sub> / I<sub>0</sub> = 1 - [(Z<sub>A</sub> - Z<sub>B</sub>)<sup>2</sup> / (Z<sub>A</sub> + Z<sub>B</sub>)<sup>2</sup>]</li> </ul> |       |
| 4(c)     | $I = I_0 e^{-\mu x}$  | C1    |
|          | $0.34 = \exp(-23 \times x)$   | C1    |
|          | x = 0.047 m   | A1    |

© UCLES 2019 Page 7 of 14

| Question | Answer  | Marks |
|----------|---|-------|
| 5(a)(i)  | loss of (signal) power/amplitude/intensity                                    | B1    |
| 5(a)(ii) | unwanted/random signal  | B1    |
|          | superposed on (transmitted) signal  | B1    |
| 5(b)(i)  | attenuation = 10 $\lg(P_2/P_1)$   | C1    |
|          | attenuation per unit length = $(1/L) \times 10 \lg(P_2/P_1)$                  | C1    |
|          | = $(1/52) \times 10 \text{ lg } [(2.5 \times 10^{-3})/(7.8 \times 10^{-16})]$ |       |
|          | = 2.4 dB km <sup>-1</sup>   | A1    |
| 5(b)(ii) | gain / dB = 10 $\lg(P_2/P_1)$   | C1    |
|          | 115 = 10 lg $[P/(7.8 \times 10^{-16})]$                                       |       |
|          | $P = 2.5 \times 10^{-4} \mathrm{W}$   | A1    |

© UCLES 2019 Page 8 of 14

| Question | Answer   | Marks |
|----------|--|-------|
| 6(a)     | work done per unit charge  | B1    |
|          | (work done) moving positive charge from infinity   | B1    |
| 6(b)     | straight line with non-zero gradient from $x = 0$ to $x = d$   | B1    |
|          | line with gradient of constant sign and end-points between which $\Delta V = V_0$ and $\Delta x = d$ | B1    |
|          | line passes through $(d, 0)$ and $(0, +V_0)$ with negative gradient throughout                       | B1    |
| 6(c)     | V constant (and non-zero) from $0 \to R$ and from $(D - R) \to D$                                    | B1    |
|          | equal (non-zero) values of (magnitude of) $V$ at $R$ and $(D-R)$ .                                   | B1    |
|          | curve (with a minimum) from $R$ to $(D-R)$ with $V$ always positive                                  | B1    |
|          | minimum at mid-point of curve  | B1    |

© UCLES 2019 Page 9 of 14

| Question | Answer  | Marks |
|----------|---|-------|
| 7(a)     | Any five from:  (as temperature rises) energy of electrons increases electrons (have enough energy to) cross forbidden band electrons enter conduction band leaving holes in valence band both holes and electrons act as charge carriers more charge carriers results in lower resistance increased lattice vibrations outweighed by increase in (number of) charge carriers | B5    |
| 7(b)     | (at 10 °C resistance is) 2.55 kΩ  | C1    |
|          | new potential difference = $9.00 \times 2.55 / (2.55 + 12.0)$   | C1    |
|          | = 1.58 V  |       |
|          | change in p.d. = 0.58 V   | A1    |
| 7(c)     | change of resistance with temperature is not linear   | B1    |
|          | change in potential with resistance is not linear  or  potential divider equation is non-linear   | B1    |

© UCLES 2019 Page 10 of 14

| Question | Answer   | Marks      |
|----------|--|------------|
| 8(a)(i)  | $v_{\rm N} = 3.4 \times 10^7 \times \sin 30^{\circ}$   | <b>A</b> 1 |
|          | $= 1.7 \times 10^7 \mathrm{ms^{-1}}$   |            |
| 8(a)(ii) | $mv^2/r = Bqv$ or $r = mv/Bq$  | C1         |
|          | $r = (9.11 \times 10^{-31} \times 1.7 \times 10^{7}) / (3.2 \times 10^{-3} \times 1.60 \times 10^{-19})$ | C1         |
|          | = 0.030 m  | A1         |
| 8(b)     | zero   | B1         |
| 8(c)     | helix/coil   | B1         |

| Question | Answer  | Marks |
|----------|---|-------|
| 9(a)(i)  | relay coil shown connected between diode and earth  | B1    |
|          | switch shown connected across lamp  | B1    |
| 9(a)(ii) | Any one from:  • (for diode to conduct) current flow is into output of op-amp  • when earth is at higher potential diode is forward biased  • diode blocks current when output positive  • diode must conduct | M1    |
|          | so $V_{OUT}$ is negative  | A1    |
| 9(b)(i)  | strain gauge  | B1    |
| 9(b)(ii) | light-dependent resistor  | B1    |

© UCLES 2019 Page 11 of 14

| Question | Answer  | Marks |
|----------|---|-------|
| 10(a)    | (induced) e.m.f. proportional to rate   | M1    |
|          | of change of (magnetic) flux (linkage)  | A1    |
| 10(b)    | current in primary coil gives rise to magnetic flux   | B1    |
|          | changing (magnetic) flux in core links with secondary coil  | B1    |
|          | induced e.m.f. (in secondary coil) causes current in load/resistor  | B1    |
| 10(c)    | correct application of turns ratio: to peak voltage ratio, giving $(V_0/220) = (450/2700)$ or to r.m.s. voltage ratio, giving $(V_{r.m.s.}/156) = (450/2700)$ | C1    |
|          | correct application of $\sqrt{2}$ factor: to peak applied e.m.f., giving 220 / $\sqrt{2}$ or to peak output em.f., giving 37 / $\sqrt{2}$                     | C1    |
|          | V <sub>r.m.s.</sub> = 26 V  | A1    |

© UCLES 2019 Page 12 of 14

| Question  | Answer  | Marks |
|-----------|---|-------|
| 11(a)     | packet/quantum of energy  | M1    |
|           | of electromagnetic radiation  | A1    |
| 11(b)(i)  | $E = hc/\lambda$  | C1    |
|           | $1.18 \times 1.60 \times 10^{-13} = (6.63 \times 10^{-34} \times 3.00 \times 10^{8}) / \lambda$ | A1    |
|           | $\lambda = 1.05 \times 10^{-12} \mathrm{m}$   |       |
| 11(b)(ii) | $\lambda = h/p$ or $E = pc$   | C1    |
|           | $p = (6.63 \times 10^{-34}) / (1.05 \times 10^{-12})$   | B1    |
|           | or $p = (1.18 \times 1.60 \times 10^{-13}) / (3.00 \times 10^{8})$                              |       |
|           | leading to $p = 6.3 \times 10^{-22} \text{N s}$   |       |
| 11(c)     | $6.3 \times 10^{-22} = 60 \times 1.66 \times 10^{-27} \times V$                                 | C1    |
|           | $v = 6.3 \times 10^3 \mathrm{ms^{-1}}$  | A1    |

© UCLES 2019 Page 13 of 14

| Question  | Answer  | Marks |
|-----------|---|-------|
| 12(a)     | energy required to separate the nucleons (in a nucleus)           | M1    |
|           | to infinity   | A1    |
|           | or  |       |
|           | energy released when nucleons come together (to form nucleus)     | (M1)  |
|           | from infinity   | (A1)  |
| 12(b)     | mass defect = $140.911 - (57 \times 1.007) - (84 \times 1.009)$   | C1    |
|           | = 140.911 – 142.155   | C1    |
|           | = (-)1.244 (u)  |       |
|           | energy = $c^2(\Delta)m$   | C1    |
|           | $= (3.00 \times 10^8)^2 \times 1.244 \times 1.66 \times 10^{-27}$ | A1    |
|           | $= 1.9 \times 10^{-10} \mathrm{J}$                                |       |
| 12(c)(i)  | $A = A_0 e^{-\lambda t}$ and $\ln 2 = \lambda t_{1/2}$            | C1    |
|           | $0.40 = \exp(-\ln 2 \times t / 3.9)$                              | C1    |
|           | or  |       |
|           | $(0.5)^n = 0.40$  | (C1)  |
|           | $n = 1.32$ and $t = 1.32 \times 3.9$                              | (C1)  |
|           | t = 5.2 hours   | A1    |
| 12(c)(ii) | daughter product may be radioactive or random nature of decay     | B1    |

© UCLES 2019 Page 14 of 14