A

A-level

Physics data and formulae

For use in exams from the June 2017 Series onwards

[Turn over]

DATA - FUNDAMENTAL CONSTANTS AND VALUES

Quantity	Symbol	Value	Units
speed of light in vacuo	c	3.00×10^{8}	$\mathrm{m\ s^{-1}}$
permeability of free space	μ_0	$4\pi \times 10^{-7}$	$\mathrm{H\ m^{-1}}$
permittivity of free space	ε_0	8.85×10^{-12}	$\mathrm{F\ m^{-1}}$
magnitude of the charge of electron	e	1.60×10^{-19}	C
the Planck constant	h	6.63×10^{-34}	J s
gravitational constant	G	6.67×10^{-11}	$\mathrm{N\ m^{2}\ kg^{-2}}$
the Avogadro constant	N_A	6.02×10^{23}	$\mathrm{mol^{-1}}$
molar gas constant	R	8.31	$\mathrm{J\ K^{-1}\ mol^{-1}}$
the Boltzmann constant	k	1.38×10^{-23}	$\mathrm{J\ K^{-1}}$
the Stefan constant	σ	5.67×10^{-8}	$\mathrm{W\ m^{-2}\ K^{-4}}$
the Wien constant	α	2.90×10^{-3}	m K
electron rest mass (equivalent to 5.5×10^{-4} u)	m_e	9.11×10^{-31}	kg

electron charge/mass ratio	$\frac{e}{m_e}$	1.76×10^{11}	$C\ kg^{-1}$
proton rest mass (equivalent to 1.00728 u)	m_p	$1.67(3) \times 10^{-27}$	kg
proton charge/mass ratio	$\frac{e}{m_p}$	9.58×10^{7}	$C\ kg^{-1}$
neutron rest mass (equivalent to 1.00867 u)	m_n	$1.67(5) \times 10^{-27}$	kg
gravitational field strength	g	9.81	$N\ kg^{-1}$
acceleration due to gravity	g	9.81	$m\ s^{-2}$
atomic mass unit (1u is equivalent to 931.5 MeV)	u	1.661×10^{-27}	kg

[Turn over]

ALGEBRAIC EQUATION

quadratic equation $x = \dfrac{-b \pm \sqrt{b^2 - 4ac}}{2a}$

ASTRONOMICAL DATA

Body	Mass/kg	Mean radius/m
Sun	1.99×10^{30}	6.96×10^{8}
Earth	5.97×10^{24}	6.37×10^{6}

GEOMETRICAL EQUATIONS

arc length	$= r\theta$
circumference of circle	$= 2\pi r$
area of circle	$= \pi r^2$
curved surface area of cylinder	$= 2\pi rh$
area of sphere	$= 4\pi r^2$
volume of sphere	$= \dfrac{4}{3}\pi r^3$

PARTICLE PHYSICS

Class	Name	Symbol	Rest energy/MeV
photon	photon	γ	0
lepton	neutrino	ν_e	0
		ν_μ	0
	electron	$e^{\pm}$	0.510999
	muon	$\mu^{\pm}$	105.659
mesons	π meson	$\pi^{\pm}$	139.576
		π^0	134.972
	K meson	$K^{\pm}$	493.821
		K^0	497.762
baryons	proton	p	938.257
	neutron	n	939.551

[Turn over]

PROPERTIES OF QUARKS
antiquarks have opposite signs

Type	Charge	Baryon number	Strangeness
u	$+\frac{2}{3}e$	$+\frac{1}{3}$	0
d	$-\frac{1}{3}e$	$+\frac{1}{3}$	0
s	$-\frac{1}{3}e$	$+\frac{1}{3}$	-1

PROPERTIES OF LEPTONS

		Lepton number
Particles:	$e^-, \nu_e ; \mu^-, \nu_\mu$	$+1$
Antiparticles:	$e^+, \overline{\nu_e}, \mu^+, \overline{\nu_\mu}$	-1

PHOTONS AND ENERGY LEVELS

photon energy $E = hf = \dfrac{hc}{\lambda}$

photoelectricity $hf = \phi + E_{k\,(max)}$

energy levels $hf = E_1 - E_2$

de Broglie wavelength $\lambda = \dfrac{h}{p} = \dfrac{h}{mv}$

[Turn over]

WAVES

wave speed $c = f\lambda$ period $f = \frac{1}{T}$

first harmonic $f = \frac{1}{2l}\sqrt{\frac{T}{\mu}}$

fringe spacing $w = \frac{\lambda D}{s}$ diffraction grating $d \sin\theta = n\lambda$

refractive index of a substance s, $n = \frac{c}{c_s}$

for two different substances of refractive indices n_1 and n_2,

law of refraction $n_1 \sin\theta_1 = n_2 \sin\theta_2$

critical angle $\sin\theta_c = \frac{n_2}{n_1}$ for $n_1 > n_2$

MECHANICS

moments	moment = Fd	
velocity and acceleration	$v = \frac{\Delta s}{\Delta t}$	$a = \frac{\Delta v}{\Delta t}$
equations of motion	$v = u + at$	$s = \left(\frac{u+v}{2}\right) t$
	$v^2 = u^2 + 2as$	$s = ut + \frac{at^2}{2}$
force	$F = ma$	
force	$F = \frac{\Delta(mv)}{\Delta t}$	
impulse	$F \Delta t = \Delta(mv)$	
work, energy and power	$W = F s \cos\theta$	
	$E_k = \frac{1}{2} m v^2$	$\Delta E_p = mg\Delta h$
	$P = \frac{\Delta W}{\Delta t}$, $P = Fv$	
	efficiency = $\frac{\text{useful output power}}{\text{input power}}$	

[Turn over]

MATERIALS

density $\rho = \frac{m}{v}$

Hooke's law $F = k\,\Delta L$

Young modulus $= \frac{\text{tensile stress}}{\text{tensile strain}}$

$\text{tensile stress} = \frac{F}{A}$

$\text{tensile strain} = \frac{\Delta L}{L}$

energy stored $E = \frac{1}{2}F\Delta L$

ELECTRICITY

current and pd $I = \frac{\Delta Q}{\Delta t}$ $V = \frac{W}{Q}$ $R = \frac{V}{I}$

resistivity $\rho = \frac{RA}{L}$

resistors in series $R_T = R_1 + R_2 + R_3 + \ldots$

resistors in parallel $\frac{1}{R_T} = \frac{1}{R_1} + \frac{1}{R_2} + \frac{1}{R_3} + \ldots$

power $P = VI = I^2R = \frac{V^2}{R}$

emf $\varepsilon = \frac{E}{Q}$ $\varepsilon = I(R + r)$

CIRCULAR MOTION

magnitude of angular speed $\omega = \frac{v}{r}$

$\omega = 2\pi f$

centripetal acceleration $a = \frac{v^2}{r} = \omega^2 r$

centripetal force $F = \frac{mv^2}{r} = m\omega^2 r$

SIMPLE HARMONIC MOTION

acceleration $a = -\omega^2 x$

displacement $x = A\cos(\omega t)$

speed $v = \pm\omega\sqrt{(A^2 - x^2)}$

maximum speed $v_{\mathrm{max}} = \omega A$

maximum acceleration $a_{\mathrm{max}} = \omega^2 A$

for a mass-spring system $T = 2\pi\sqrt{\frac{m}{k}}$

for a simple pendulum $T = 2\pi\sqrt{\frac{l}{g}}$

[Turn over]

THERMAL PHYSICS

energy to change temperature	$Q = mc\Delta\theta$
energy to change state	$Q = ml$
gas law	$pV = nRT$ $pV = NkT$
kinetic theory model	$pV = \frac{1}{3}Nm\,(c_{\mathrm{rms}})^2$
kinetic energy of gas molecule	$\frac{1}{2}m\,(c_{\mathrm{rms}})^2 = \frac{3}{2}kT = \frac{3RT}{2N_{\mathrm{A}}}$

GRAVITATIONAL FIELDS

force between two masses	$F = \frac{Gm_1m_2}{r^2}$
gravitational field strength	$g = \frac{F}{m}$
magnitude of gravitational field strength in a radial field	$g = \frac{GM}{r^2}$
work done	$\Delta W = m\Delta V$
gravitational potential	$V = -\frac{GM}{r}$
	$g = -\frac{\Delta V}{\Delta r}$

ELECTRIC FIELDS AND CAPACITORS

force between two point charges	$F = \dfrac{1}{4\pi\varepsilon_0} \dfrac{Q_1Q_2}{r^2}$
force on a charge	$F = EQ$
field strength for a uniform field	$E = \dfrac{V}{d}$
work done	$\Delta W = Q\Delta V$
field strength for a radial field	$E = \dfrac{1}{4\pi\varepsilon_0} \dfrac{Q}{r^2}$
electric potential	$V = \dfrac{1}{4\pi\varepsilon_0} \dfrac{Q}{r}$
field strength	$E = \dfrac{\Delta V}{\Delta r}$
capacitance	$C = \dfrac{Q}{V}$
	$C = \dfrac{A\varepsilon_0\varepsilon_r}{d}$
capacitor energy stored	$E = \dfrac{1}{2}QV = \dfrac{1}{2}CV^2 = \dfrac{1}{2}\dfrac{Q^2}{C}$

[Turn over]

capacitor charging	$Q = Q_0(1 - e^{-\frac{t}{RC}})$
decay of charge	$Q = Q_0 e^{-\frac{t}{RC}}$
time constant	RC

MAGNETIC FIELDS

force on a current	$F = BIl$
force on a moving charge	$F = BQv$
magnetic flux	$\Phi = BA$
magnetic flux linkage	$N\Phi = BAN\cos\theta$
magnitude of induced emf	$\varepsilon = N\dfrac{\Delta\Phi}{\Delta t}$
	$N\Phi = BAN\cos\theta$
emf induced in a rotating coil	$\varepsilon = BAN\omega\sin\omega t$
alternating current	$I_{\mathrm{rms}} = \dfrac{I_0}{\sqrt{2}}$ $V_{\mathrm{rms}} = \dfrac{V_0}{\sqrt{2}}$
transformer equations	$\dfrac{N_{\mathrm{s}}}{N_{\mathrm{p}}} = \dfrac{V_{\mathrm{s}}}{V_{\mathrm{p}}}$
	efficiency $= \dfrac{I_{\mathrm{s}}V_{\mathrm{s}}}{I_{\mathrm{p}}V_{\mathrm{p}}}$

NUCLEAR PHYSICS

inverse square law for γ radiation	$I = \frac{k}{x^2}$
radioactive decay	$\frac{\Delta N}{\Delta t} = -\lambda N$, $N = N_0 e^{-\lambda t}$
activity	$A = \lambda N$
half-life	$T_{½} = \frac{\ln 2}{\lambda}$
nuclear radius	$R = R_0 A^{1/3}$
energy-mass equation	$E = mc^2$

[Turn over]

OPTIONS

ASTROPHYSICS

1 astronomical unit = 1.50×10^{11} m

1 light year = 9.46×10^{15} m

1 parsec = 2.06×10^{5} AU = 3.08×10^{16} m = 3.26 ly

Hubble constant, $H = 65\ \text{km s}^{-1}\ \text{Mpc}^{-1}$

$$M = \frac{\text{angle subtended by image at eye}}{\text{angle subtended by object at unaided eye}}$$

telescope in normal adjustment $M = \dfrac{f_0}{f_e}$

Rayleigh criterion $\theta \approx \dfrac{\lambda}{D}$

magnitude equation $m - M = 5 \log \dfrac{d}{10}$

Wien's law $\lambda_{max} T = 2.9 \times 10^{-3}$ m K

Stefan's law $P = \sigma A T^4$

Schwarzschild radius $R_S \approx \dfrac{2GM}{c^2}$

Doppler shift for $v << c$ $$\frac{\Delta f}{f} = -\frac{\Delta \lambda}{\lambda} = \frac{v}{c}$$

red shift $$z = -\frac{v}{c}$$

Hubble's law $$v = Hd$$

[Turn over]

MEDICAL PHYSICS

lens equations $P = \frac{1}{f}$

$m = \frac{v}{u}$

$\frac{1}{f} = \frac{1}{u} + \frac{1}{v}$

threshold of hearing $I_0 = 1.0 \times 10^{-12}\ \mathrm{W\,m^{-2}}$

intensity level $\textit{intensity level} = 10 \log \frac{I}{I_0}$

absorption $I = I_0 e^{-\mu x}$

$\mu_\mathrm{m} = \frac{\mu}{\rho}$

ultrasound imaging $Z = \rho c$

$\frac{I_\mathrm{r}}{I_\mathrm{i}} = \left(\frac{Z_2 - Z_1}{Z_2 + Z_1}\right)^2$

half-lives $\frac{1}{T_\mathrm{E}} = \frac{1}{T_\mathrm{B}} + \frac{1}{T_\mathrm{P}}$

ENGINEERING PHYSICS

moment of inertia	$I = \Sigma m r^2$
angular kinetic energy	$E_k = \frac{1}{2} I \omega^2$
equations of angular motion	$\omega_2 = \omega_1 + \alpha t$
	$\omega_2{}^2 = \omega_1{}^2 + 2\alpha\theta$
	$\theta = \omega_1 t + \frac{\alpha t^2}{2}$
	$\theta = \frac{(\omega_1 + \omega_2)\, t}{2}$
torque	$T = I \alpha$
	$T = F r$
angular momentum	angular momentum = $I\omega$
angular impulse	$T\Delta t = \Delta(I\omega)$
work done	$W = T\theta$
power	$P = T\omega$
thermodynamics	$Q = \Delta U + W$
	$W = p\Delta V$
adiabatic change	pV^{γ} = constant
isothermal change	pV = constant

[Turn over]

heat engines

$$\text{efficiency} = \frac{W}{Q_\text{H}} = \frac{Q_\text{H} - Q_\text{C}}{Q_\text{H}}$$

$$\text{maximum theoretical efficiency} = \frac{T_\text{H} - T_\text{C}}{T_\text{H}}$$

work done per cycle = area of loop

input power = calorific value × fuel flow rate

indicated power = (area of $p - V$ loop)
× (number of cycles per second)
× (number of cylinders)

output or brake power $P = T\omega$

friction power = indicated power − brake power

heat pumps and refrigerators

$$\text{refrigerator: } COP_\text{ref} = \frac{Q_\text{C}}{W} = \frac{Q_\text{C}}{Q_\text{H} - Q_\text{C}}$$

$$\text{heat pump: } COP_\text{hp} = \frac{Q_\text{H}}{W} = \frac{Q_\text{H}}{Q_\text{H} - Q_\text{C}}$$

TURNING POINTS IN PHYSICS

electrons in fields

$$F = \frac{eV}{d}$$

$$F = Bev$$

$$r = \frac{mv}{Be}$$

$$\tfrac{1}{2} mv^2 = eV$$

Millikan's experiment

$$\frac{QV}{d} = mg$$

$$F = 6\pi\eta rv$$

Maxwell's formula

$$c = \frac{1}{\sqrt{\mu_0\, \varepsilon_0}}$$

$$\lambda = \frac{h}{p} = \frac{h}{\sqrt{2meV}}$$

[Turn over]

special relativity	$t = \dfrac{t_0}{\sqrt{1 - \dfrac{v^2}{c^2}}}$
	$l = l_0 \sqrt{1 - \dfrac{v^2}{c^2}}$
	$E = m\,c^2 = \dfrac{m_0 c^2}{\sqrt{1 - \dfrac{v^2}{c^2}}}$

ELECTRONICS

resonant frequency	$f_0 = \dfrac{1}{2\pi\sqrt{LC}}$
Q-factor	$Q = \dfrac{f_0}{f_B}$
operational amplifiers: open loop	$V_{out} = A_{OL}\,(V_+ - V_-)$
inverting amplifier	$\dfrac{V_{out}}{V_{in}} = -\dfrac{R_f}{R_{in}}$

non-inverting amplifier

$$\frac{V_{\text{out}}}{V_{\text{in}}} = 1 + \frac{R_{\text{f}}}{R_1}$$

summing amplifier

$$V_{\text{out}} = -R_{\text{f}} \left(\frac{V_1}{R_1} + \frac{V_2}{R_2} + \frac{V_3}{R_3} + \dots \right)$$

difference amplifier

$$V_{\text{out}} = (V_+ - V_-) \frac{R_{\text{f}}}{R_1}$$

Bandwidth requirement:

for AM bandwidth = $2f_{\text{M}}$

for FM bandwidth = $2(\Delta f + f_{\text{M}})$

END OF FORMULAE

There are no formulae printed on this page

IB/M/Jun17/CD/7408/INS/E6